



### Main

Aesthetic name	Unica KNX
Product or component type	Movement detector
Device presentation	Mechanism
Cover plate colour tint	Aluminium

### Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Movement detection area	9 x 9 m(PIR mounting height 2.15m)
Detection angle	Full 180°
Number of modules	2 modules
Light intensity adjustment	10...< 1000 lux @rotary switch 10...2000 lux @ETS
Time delay	Rotary switch : 1 s...8 min ETS : 1 s...255 h
Number of cables	2 flexible : <= 2.5 mm <sup>2</sup> 2 rigid : <= 2.5 mm <sup>2</sup>
Connections - terminals	Screwless terminals
Fixing mode	Clip-in
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Mounting height	1...2.5 m
Embedding depth	34 mm
Depth	56 mm

### Environment

IP degree of protection	IP20
Ambient air temperature for operation	-5...45 °C
Environmental characteristic	Acetone Alcohol

Ammonia  
Bleach  
Liquid soap  
Oil  
Petrol  
UV resistant  
Window-cleaning fluid

---

Environmental health and issues	Halogen free
Standards	EMC directive LV directive

---

### Offer Sustainability

---

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1342 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>

---

### Contractual warranty

---

Warranty period	18 months
-----------------	-----------

---