



Main

| | |
|---------------------------|--|
| Range of product | KNX |
| Aesthetic name | M-Arc M-Elegance M-Plan M-Plan glass M-Smart M-Star System M |
| Product or component type | Movement sensor |
| Bus type | KNX |
| Number of channels | 5 |
| Colour tint | Active white glossy |
| Colour code | RAL 9016 |

Complementary

| | |
|----------------------------|------------------------------|
| Type of setting | Light sensitivity adjustable |
| Wiring device mounting | Flush |
| Mounting height | 2.5 m |
| Duty cycle | 15300 minutes |
| Time delay | 1 second switch-on |
| Movement detection area | 16 m |
| Horizontal detection angle | 0...180 ° |
| Detection face | Lateral 8 m |
| Protection type | Creep zone protection |
| Material | Plastic brilliant |
| Surface treatment | Antibacterial |

Environment

| | |
|---------------------------------|--------------|
| Environmental health and issues | Halogen free |
|---------------------------------|--------------|

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1342 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|