



Main

Aesthetic name	Unica KNX
Product or component type	Movement detector
Device presentation	Mechanism
Cover plate colour tint	Ivory

Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Movement detection area	9 x 9 m(PIR mounting height 2.15m)
Detection angle	Full 180°
Number of modules	2 modules
Light intensity adjustment	10...< 1000 lux @rotary switch 10...2000 lux @ETS
Time delay	Rotary switch : 1 s...8 min ETS : 1 s...255 h
Number of cables	2 flexible : <= 2.5 mm ² 2 rigid : <= 2.5 mm ²
Connections - terminals	Screwless terminals
Fixing mode	Clip-in
Material	Mechanism cover : ASA + PC Fixing frame : zamak
Mounting height	1...2.5 m
Embedding depth	34 mm
Depth	56 mm

Environment

IP degree of protection	IP20
Ambient air temperature for operation	-5...45 °C
Environmental characteristic	Acetone Alcohol

Ammonia
Bleach
Liquid soap
Oil
Petrol
UV resistant
Window-cleaning fluid

Environmental health and issues	Halogen free
Standards	EMC directive LV directive

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1342 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months
-----------------	-----------
