



### Main

Aesthetic name	Unica KNX
Product or component type	Switch
Device presentation	Mechanism
Switch function	2-way
Transmission support medium	Infrared
Rated current	10 A, 250 V AC, 50/60 Hz
Actuator	Push-button
Number of modules	2 modules
Fixing mode	Screws
Cover plate colour tint	White

### Complementary

Contacts type and composition	2 NO
Opening distance	> 3 mm
Pilot light	Blue LED : 1 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	<= 2.5 mm <sup>2</sup> (flexible) <= 2.5 mm <sup>2</sup> (rigid)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Standards	EMC directive LV directive
Ambient air temperature for operation	-5...45 °C

### Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone

Alcohol  
Ammonia  
Bleach  
Liquid soap  
Oil  
Petrol  
UV resistant  
Window-cleaning fluid

---

Environmental health and issues      Halogen free

---

### Offer Sustainability

---

Sustainable offer status      Green Premium product

---

RoHS (date code: YYWW)      Compliant - since 1426 - Schneider Electric declaration of conformity  
[📄 Schneider Electric declaration of conformity](#)

---

REACH      Reference not containing SVHC above the threshold  
[Reference not containing SVHC above the threshold](#)

---

Product environmental profile      Available  
[📄 Product environmental](#)

---

Product end of life instructions      Need no specific recycling operations  
[📄 End of life manual](#)

---

### Contractual warranty

---

Warranty period      18 months

---