



### Main

Range of product	Unica
Aesthetic name	Unica KNX
Product or component type	Room temperature control unit
Device presentation	Mechanism
Cover plate colour tint	Aluminium

### Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Number of modules	2 modules
Device composition	Display 4 buttons
Number of cables	2 flexible : $\leq 2.5 \text{ mm}^2$ 2 rigid : $\leq 2.5 \text{ mm}^2$
Contacts type and composition	1 C/O
Connections - terminals	Screwless terminals
Information displayed	Day Time Operating mode Temperature
Status LED	Programming LED
Programmable temperature	No
Temperature setting range	0...40 °C
Measurement accuracy	$\pm 1 \text{ K}$
Fixing mode	Clip-in
Mounting height	> 1.5 m
Depth	39 mm
Embedding depth	26 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	-5...45 °C
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Product certifications	Aenor CE
Standards	EMC directive LV directive

## Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 4Q2019 <a href="#">Will be compliant on 4Q2019</a>
REACH	Reference contains SVHC above the threshold - Go to CaP for more details <a href="#">Go to CaP for more details</a>
Product environmental profile	Available <a href="#">Product environmental</a>
Product end of life instructions	Available <a href="#">End of life manual</a>

## Contractual warranty

Warranty period	18 months
-----------------	-----------