



Main

Range of product	Unica
Aesthetic name	Unica KNX
Product or component type	Room temperature control unit
Device presentation	Mechanism
Cover plate colour tint	White

Complementary

[Ue] rated operational voltage	230 V AC (+/- 10 %), 50/60 Hz
Number of modules	2 modules
Device composition	Display 4 buttons
Number of cables	2 flexible : $\leq 2.5 \text{ mm}^2$ 2 rigid : $\leq 2.5 \text{ mm}^2$
Contacts type and composition	1 C/O
Connections - terminals	Screwless terminals
Information displayed	Day Time Operating mode Temperature
Status LED	Programming LED
Programmable temperature	No
Temperature setting range	0...40 °C
Measurement accuracy	$\pm 1 \text{ K}$
Fixing mode	Clip-in
Mounting height	> 1.5 m
Depth	39 mm
Embedding depth	26 mm

Environment

IP degree of protection	IP20
IK degree of protection	IK01
Ambient air temperature for operation	-5...45 °C
Environmental characteristic	Acetone Alcohol Ammonia Bleach Liquid soap Oil Petrol UV resistant Window-cleaning fluid
Environmental health and issues	Halogen free
Product certifications	Aenor CE
Standards	EMC directive LV directive

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 4Q2019 Will be compliant on 4Q2019
REACH	Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details
Product environmental profile	Available Product environmental
Product end of life instructions	Available End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------