



Main

| | |
|---------------------------|-----------------|
| Range of product | KNX |
| Product or component type | Movement sensor |
| Bus type | KNX |
| Number of channels | 20 5 |
| Colour tint | Dark brazil |
| Colour code | RAL 8019 |

Complementary


| | |
|----------------------------|------------------------------|
| Type of setting | Light sensitivity adjustable |
| Wiring device mounting | Surface |
| Mounting height | 2.5 m |
| Duty cycle | 9144 minutes |
| Time delay | 1 second switch-on |
| Detection face | Lateral 12 m |
| Movement detection area | 24 m |
| Horizontal detection angle | 0...220 ° |
| Protection type | Creep zone protection |

Environment

| | |
|---------------------------------|--------------|
| Environmental health and issues | Halogen free |
|---------------------------------|--------------|

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1342 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference contains SVHC above the threshold - Go to CaP for more details Go to CaP for more details |

| | |
|-------------------------------|--|
| Product environmental profile | Available  Product environmental |
|-------------------------------|--|

| | |
|----------------------------------|-----------|
| Product end of life instructions | Available |
|----------------------------------|-----------|

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
